

**BI-DIRECTIONAL CURRENT TRANSDUCERS**

PROVIDE AN ISOLATED BI-POLAR OUTPUT DIRECTLY PROPORTIONAL TO THE INPUT CURRENT. THE OUTPUT SIGNAL TRACKS THE INPUT CURRENT WAVEFORM AND RECREATES ALMOST ANY AC, DC, TRANSIENT OR COMPLEX CURRENT COMBINATION.

Series No.

[905B](#) [909M4](#) [926](#) [929](#) [943](#) [944](#) [947](#) [948](#) [9000](#) [S273](#)  
[S449](#) [S630](#) [S651](#) [S661B](#) [S745](#) [S764](#) [S784](#)

**DC CURRENT TRANSDUCERS**

MONITOR DC CURRENT BY PROVIDING A MAGNETICALLY ISOLATED ANALOG OUTPUT THAT IS DIRECTLY PROPORTIONAL TO THE INPUT. LOW CURRENT RANGES ARE AVAILABLE FOR DIFFERENTIAL AND GROUND FAULT CURRENT MONITORING.

Series No.

[903B](#) [904B](#) [913A](#) [913B](#) [920](#) [921](#) [936](#) [950](#) [952](#) [S218](#)  
[S347](#) [S444](#) [S966](#) [S465](#) [S619](#) [S646](#) [S728B](#) [S767](#) [S770](#)

**DC CURRENT DETECTORS**

COMPARES THE DC INPUT TO A FIXED OR ADJUSTABLE CURRENT LIMIT. THE OUTPUT IS AN ISOLATED SWITCH OR RELAY THAT ACTIVATES AS REQUIRED. DC CURRENT DETECTORS ARE SUITED FOR GROUND FAULT CURRENT MONITORING.

Series No.

[901B](#) [S58](#) [S201](#) [S204](#) [S623](#) [S629](#) [S680](#) [S754](#)

**AC CURRENT TRANSDUCERS**

MAINTAIN ISOLATION AND PROVIDE AN ANALOG DC OUTPUT DIRECTLY PROPORTIONAL TO AC INPUT CURRENT. TRUE-RMS AND AVERAGE RESPONDING PRODUCTS ARE AVAILABLE IN CLAMP-ON AND PASS-THRU CONFIGURATIONS.

Series No.

[1001](#) [1002M1](#) [1003AM1](#) [1003AM2](#) [1004](#) [1005](#) [1006](#)  
[1006X](#) [1055](#) [1055L](#) [1070](#) [C](#) [CX](#) [S383](#) [S383L](#) [S402](#)  
[S461](#) [S714](#) [S786](#)

**AC CURRENT DETECTORS**

COMPARES THE AC INPUT TO A FIXED OR ADJUSTABLE CURRENT LIMIT. THE OUTPUT IS AN ISOLATED SWITCH OR RELAY THAT IS ACTIVATED AS REQUIRED. PRODUCTS AVAILABLE IN CLAMP-ON AND PASS-THRU CONFIGURATIONS.

Series No.

[870](#) [871](#) [880B](#) [881](#) [882](#) [S212](#)

**AC VOLTAGE TRANSDUCERS**

PRODUCE AN ISOLATED ANALOG OUTPUT SIGNAL DIRECTLY PROPORTIONAL TO AC VOLTAGE AT A VARIETY OF FREQUENCIES. HIGH SENSITIVITY VERSIONS ARE AVAILABLE WITH ZERO SUPPRESSED AC INPUT VOLTAGE RANGES.

Series No.

[101M3](#) [102M3](#) [105](#) [108](#) [108X](#) [V](#) [VX](#) [S190](#)

**DC VOLTAGE TRANSDUCER & DETECTOR**

SERIES S657 PRODUCES AN ISOLATED ANALOG OUTPUT PROPORTIONAL TO DC VOLTAGE. SERIES S631 COMPARES THE DC INPUT TO AN ADJUSTABLE THRESHOLD. THE OUTPUT IS AN ISOLATED RELAY THAT ACTIVATES AS REQUIRED.

Series No.

[S631](#) [S657](#)

**AC POWER TRANSDUCERS**

PROVIDES AN ISOLATED ANALOG DC OUTPUT DIRECTLY PROPORTIONAL TO AC INPUT POWER. TRUE POWER (WATTS) AND VOLT-AMP-REACTIVE (VAR) TRANSDUCERS ARE AVAILABLE FOR A VARIETY OF POWER RANGES AND FREQUENCIES.

Series No.

[415A](#) [416A](#) [S73](#) [S217](#) [W&Q](#)

**FREQUENCY TRANSDUCERS**

PROVIDES AN ISOLATED ANALOG DC OUTPUT SIGNAL DIRECTLY PROPORTIONAL TO AC INPUT FREQUENCY. MANY RANGES ARE AVAILABLE, STARTING AT 5 TO 100HZ AND ALL THE WAY UP TO 1K TO 20KHZ.

Series No.

[S343](#) [S350L](#)

***For other products including  
modified standard & custom specials***

Visit <http://www.a-a-c.com>

email [aac@rcn.com](mailto:aac@rcn.com)

or call toll-free

(888) 873-8559

***Thank you.***

DATA SHEETS AT  
[www.a-a-c.com](http://www.a-a-c.com)

### BI-DIRECTIONAL CURRENT TRANSDUCERS

SEVENTEEN MODELS IN ORDER OF CURRENT RANGE

PAGE  
2 OF 13

	<p><b>SERIES 905B</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER <math>\pm 15VDC</math>; TEMPERATURE <math>-55^{\circ}</math> TO <math>+85^{\circ}C</math>; APERTURE 3/8 INCH DIA; RESPONSE 50m-SEC; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS.</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 50MA</math></td> <td>0 TO <math>\pm 1A</math></td> </tr> <tr> <td>0 TO <math>\pm 100MA</math></td> <td>0 TO <math>\pm 2A</math></td> </tr> <tr> <td>0 TO <math>\pm 200MA</math></td> <td>0 TO <math>\pm 5A</math></td> </tr> <tr> <td>0 TO <math>\pm 500MA</math></td> <td></td> </tr> </table>	0 TO $\pm 50MA$	0 TO $\pm 1A$	0 TO $\pm 100MA$	0 TO $\pm 2A$	0 TO $\pm 200MA$	0 TO $\pm 5A$	0 TO $\pm 500MA$	
0 TO $\pm 50MA$	0 TO $\pm 1A$									
0 TO $\pm 100MA$	0 TO $\pm 2A$									
0 TO $\pm 200MA$	0 TO $\pm 5A$									
0 TO $\pm 500MA$										
	<p><b>SERIES S661B</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER <math>\pm 15VDC</math>; TEMPERATURE <math>-40^{\circ}</math> TO <math>+85^{\circ}C</math>; APERTURE 3/4 INCH DIA; FREQUENCY DC TO 60HZ; RESPONSE 1m-SEC; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 100MA</math></td> <td>0 TO <math>\pm 400MA</math></td> </tr> <tr> <td>0 TO <math>\pm 200MA</math></td> <td>0 TO <math>\pm 500MA</math></td> </tr> <tr> <td>0 TO <math>\pm 250MA</math></td> <td>0 TO <math>\pm 750MA</math></td> </tr> <tr> <td>0 TO <math>\pm 300MA</math></td> <td>0 TO <math>\pm 1A</math></td> </tr> </table>	0 TO $\pm 100MA$	0 TO $\pm 400MA$	0 TO $\pm 200MA$	0 TO $\pm 500MA$	0 TO $\pm 250MA$	0 TO $\pm 750MA$	0 TO $\pm 300MA$	0 TO $\pm 1A$
0 TO $\pm 100MA$	0 TO $\pm 400MA$									
0 TO $\pm 200MA$	0 TO $\pm 500MA$									
0 TO $\pm 250MA$	0 TO $\pm 750MA$									
0 TO $\pm 300MA$	0 TO $\pm 1A$									
	<p><b>SERIES 926</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE: OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.25%FS; POWER +24 TO 32VDC; TEMPERATURE <math>-55^{\circ}</math> TO <math>+85^{\circ}C</math>; APERTURE 3/8 INCH DIA; RESPONSE 5m-SEC; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 5A</math></td> <td>0 TO <math>\pm 20A</math></td> </tr> <tr> <td>0 TO <math>\pm 10A</math></td> <td>0 TO <math>\pm 25A</math></td> </tr> <tr> <td>0 TO <math>\pm 15A</math></td> <td></td> </tr> </table>	0 TO $\pm 5A$	0 TO $\pm 20A$	0 TO $\pm 10A$	0 TO $\pm 25A$	0 TO $\pm 15A$			
0 TO $\pm 5A$	0 TO $\pm 20A$									
0 TO $\pm 10A$	0 TO $\pm 25A$									
0 TO $\pm 15A$										
	<p><b>SERIES S764</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER +12 TO 36VDC; TEMPERATURE <math>-40^{\circ}</math> TO <math>+85^{\circ}C</math>; APERTURE 3/4 INCH DIA; RESPONSE 1m-SEC; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 20A</math></td> <td>0 TO <math>\pm 50A</math></td> </tr> <tr> <td>0 TO <math>\pm 25A</math></td> <td>0 TO <math>\pm 60A</math></td> </tr> <tr> <td>0 TO <math>\pm 30A</math></td> <td>0 TO <math>\pm 70A</math></td> </tr> <tr> <td>0 TO <math>\pm 40A</math></td> <td>0 TO <math>\pm 100A</math></td> </tr> </table>	0 TO $\pm 20A$	0 TO $\pm 50A$	0 TO $\pm 25A$	0 TO $\pm 60A$	0 TO $\pm 30A$	0 TO $\pm 70A$	0 TO $\pm 40A$	0 TO $\pm 100A$
0 TO $\pm 20A$	0 TO $\pm 50A$									
0 TO $\pm 25A$	0 TO $\pm 60A$									
0 TO $\pm 30A$	0 TO $\pm 70A$									
0 TO $\pm 40A$	0 TO $\pm 100A$									
	<p><b>SERIES S273</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 15VDC</math>; FREQUENCY DC-100KHZ; RESPONSE 1<math>\mu</math>-SEC; TEMPERATURE <math>-55^{\circ}</math> TO <math>+85^{\circ}C</math>; APERTURE 3/4 INCH DIA; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 25A</math></td> <td>0 TO <math>\pm 200A</math></td> </tr> <tr> <td>0 TO <math>\pm 50A</math></td> <td>0 TO <math>\pm 250A</math></td> </tr> <tr> <td>0 TO <math>\pm 100A</math></td> <td>0 TO <math>\pm 300A</math></td> </tr> <tr> <td>0 TO <math>\pm 150A</math></td> <td>0 TO <math>\pm 350A</math></td> </tr> </table>	0 TO $\pm 25A$	0 TO $\pm 200A$	0 TO $\pm 50A$	0 TO $\pm 250A$	0 TO $\pm 100A$	0 TO $\pm 300A$	0 TO $\pm 150A$	0 TO $\pm 350A$
0 TO $\pm 25A$	0 TO $\pm 200A$									
0 TO $\pm 50A$	0 TO $\pm 250A$									
0 TO $\pm 100A$	0 TO $\pm 300A$									
0 TO $\pm 150A$	0 TO $\pm 350A$									
	<p><b>SERIES S449</b> ▶ <a href="#">Data Sheet</a></p> <p>SPACE FLIGHT; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 15VDC</math>; FREQUENCY DC-100KHZ; RESPONSE 1<math>\mu</math>-SEC; TEMPERATURE <math>-40^{\circ}</math> TO <math>+71^{\circ}C</math>; APERTURE 1/4 INCH DIA; SOLDER HEADER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 25A</math></td> <td>0 TO <math>\pm 50A</math></td> </tr> <tr> <td>0 TO <math>\pm 40A</math></td> <td>0 TO <math>\pm 60A</math></td> </tr> </table>	0 TO $\pm 25A$	0 TO $\pm 50A$	0 TO $\pm 40A$	0 TO $\pm 60A$				
0 TO $\pm 25A$	0 TO $\pm 50A$									
0 TO $\pm 40A$	0 TO $\pm 60A$									
	<p><b>SERIES S745</b> ▶ <a href="#">Data Sheet</a></p> <p>SPACE FLIGHT; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 12VDC</math>; FREQUENCY DC-20KHZ; RESPONSE 1-2<math>\mu</math>-SEC; TEMPERATURE <math>-55^{\circ}</math> TO <math>+100^{\circ}C</math>; APERTURE 3/8 INCH DIA; METAL CASE; WEIGHT 8OZ.; SOLDER HEADER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 40A</math></td> <td>0 TO <math>\pm 150A</math></td> </tr> <tr> <td>0 TO <math>\pm 75A</math></td> <td>0 TO <math>\pm 250A</math></td> </tr> </table>	0 TO $\pm 40A$	0 TO $\pm 150A$	0 TO $\pm 75A$	0 TO $\pm 250A$				
0 TO $\pm 40A$	0 TO $\pm 150A$									
0 TO $\pm 75A$	0 TO $\pm 250A$									
	<p><b>SERIES 929</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS (OVER TEMPERATURE); POWER +10VDC TO +34VDC; FREQUENCY DC-350KHZ; RESPONSE 1<math>\mu</math>-SEC; TEMPERATURE <math>-40^{\circ}</math> TO <math>+85^{\circ}C</math>; APERTURE 3/4 INCH DIA; CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 50A</math></td> <td>0 TO <math>\pm 200A</math></td> </tr> <tr> <td>0 TO <math>\pm 75A</math></td> <td>0 TO <math>\pm 250A</math></td> </tr> <tr> <td>0 TO <math>\pm 100A</math></td> <td>0 TO <math>\pm 300A</math></td> </tr> <tr> <td>0 TO <math>\pm 150A</math></td> <td>0 TO <math>\pm 400A</math></td> </tr> </table>	0 TO $\pm 50A$	0 TO $\pm 200A$	0 TO $\pm 75A$	0 TO $\pm 250A$	0 TO $\pm 100A$	0 TO $\pm 300A$	0 TO $\pm 150A$	0 TO $\pm 400A$
0 TO $\pm 50A$	0 TO $\pm 200A$									
0 TO $\pm 75A$	0 TO $\pm 250A$									
0 TO $\pm 100A$	0 TO $\pm 300A$									
0 TO $\pm 150A$	0 TO $\pm 400A$									
	<p><b>SERIES S651</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER +22 TO +32VDC; FREQUENCY DC-3.5KHZ; RESPONSE 100<math>\mu</math>-SEC; TEMPERATURE <math>-40^{\circ}</math> TO <math>+65^{\circ}C</math>; APERTURE 1+3/8 INCH DIA; CONNECTOR TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 100A</math></td> <td>0 TO <math>\pm 200A</math></td> </tr> </table>	0 TO $\pm 100A$	0 TO $\pm 200A$						
0 TO $\pm 100A$	0 TO $\pm 200A$									

DATA SHEETS AT

[www.a-a-c.com](http://www.a-a-c.com)

### BI-DIRECTIONAL CURRENT TRANSDUCERS








CONTINUED (PART TWO OF TWO)

PAGE  
3 of 13

	<p><b>SERIES S784</b> ▶ <a href="#">Data Sheet</a></p> <p>AIRCRAFT DO-160; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER +16 TO 40VDC; FREQUENCY DC-1KHZ; RESPONSE 500<math>\mu</math>-SEC; TEMPERATURE -40° TO +85°C; APERTURE 3/4 INCH DIA; METAL CASE; WEIGHT 9OZ.; SOLDER HEADER TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 100A</math></td> <td>0 TO <math>\pm 400A</math></td> </tr> <tr> <td>0 TO <math>\pm 200A</math></td> <td>0 TO <math>\pm 500A</math></td> </tr> <tr> <td>0 TO <math>\pm 250A</math></td> <td>0 TO <math>\pm 600A</math></td> </tr> <tr> <td>0 TO <math>\pm 300A</math></td> <td>0 TO <math>\pm 750A</math></td> </tr> </table>	0 TO $\pm 100A$	0 TO $\pm 400A$	0 TO $\pm 200A$	0 TO $\pm 500A$	0 TO $\pm 250A$	0 TO $\pm 600A$	0 TO $\pm 300A$	0 TO $\pm 750A$		
0 TO $\pm 100A$	0 TO $\pm 400A$											
0 TO $\pm 200A$	0 TO $\pm 500A$											
0 TO $\pm 250A$	0 TO $\pm 600A$											
0 TO $\pm 300A$	0 TO $\pm 750A$											
	<p><b>SERIES 947</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 15VDC</math>; FREQUENCY DC-100KHZ; RESPONSE 1<math>\mu</math>-SEC; TEMPERATURE -20° TO +70°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 100A</math></td> <td>0 TO <math>\pm 400A</math></td> </tr> <tr> <td>0 TO <math>\pm 200A</math></td> <td>0 TO <math>\pm 500A</math></td> </tr> <tr> <td>0 TO <math>\pm 300A</math></td> <td>0 TO <math>\pm 600A</math></td> </tr> </table>	0 TO $\pm 100A$	0 TO $\pm 400A$	0 TO $\pm 200A$	0 TO $\pm 500A$	0 TO $\pm 300A$	0 TO $\pm 600A$				
0 TO $\pm 100A$	0 TO $\pm 400A$											
0 TO $\pm 200A$	0 TO $\pm 500A$											
0 TO $\pm 300A$	0 TO $\pm 600A$											
	<p><b>SERIES 943A</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 15VDC</math>; FREQUENCY DC-100KHZ; RESPONSE 1<math>\mu</math>-SEC; TEMPERATURE -55° TO +85°C; APERTURE 1+3/8 INCH DIA; METAL CASE; BARRIER OR CONNECTOR TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 100A</math></td> <td>0 TO <math>\pm 600A</math></td> </tr> <tr> <td>0 TO <math>\pm 200A</math></td> <td>0 TO <math>\pm 750A</math></td> </tr> <tr> <td>0 TO <math>\pm 300A</math></td> <td>0 TO <math>\pm 800A</math></td> </tr> <tr> <td>0 TO <math>\pm 400A</math></td> <td>0 TO <math>\pm 1000A</math></td> </tr> <tr> <td>0 TO <math>\pm 500A</math></td> <td></td> </tr> </table>	0 TO $\pm 100A$	0 TO $\pm 600A$	0 TO $\pm 200A$	0 TO $\pm 750A$	0 TO $\pm 300A$	0 TO $\pm 800A$	0 TO $\pm 400A$	0 TO $\pm 1000A$	0 TO $\pm 500A$	
0 TO $\pm 100A$	0 TO $\pm 600A$											
0 TO $\pm 200A$	0 TO $\pm 750A$											
0 TO $\pm 300A$	0 TO $\pm 800A$											
0 TO $\pm 400A$	0 TO $\pm 1000A$											
0 TO $\pm 500A$												
	<p><b>SERIES 944</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 15VDC</math>; FREQUENCY DC-20KHZ; TEMPERATURE -55° TO +85°C; APERTURE 1+3/8 INCH DIA; METAL CASE; BARRIER SCREW OR CONNECTOR TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 600A</math></td> <td>0 TO <math>\pm 1500A</math></td> </tr> <tr> <td>0 TO <math>\pm 800A</math></td> <td>0 TO <math>\pm 2000A</math></td> </tr> <tr> <td>0 TO <math>\pm 1000A</math></td> <td></td> </tr> </table>	0 TO $\pm 600A$	0 TO $\pm 1500A$	0 TO $\pm 800A$	0 TO $\pm 2000A$	0 TO $\pm 1000A$					
0 TO $\pm 600A$	0 TO $\pm 1500A$											
0 TO $\pm 800A$	0 TO $\pm 2000A$											
0 TO $\pm 1000A$												
	<p><b>SERIES 948</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 0.5%FS; POWER <math>\pm 15VDC</math>; FREQUENCY DC-20KHZ; TEMPERATURE -20° TO +70°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 600A</math></td> <td>0 TO <math>\pm 1500A</math></td> </tr> <tr> <td>0 TO <math>\pm 800A</math></td> <td>0 TO <math>\pm 2000A</math></td> </tr> <tr> <td>0 TO <math>\pm 1000A</math></td> <td></td> </tr> </table>	0 TO $\pm 600A$	0 TO $\pm 1500A$	0 TO $\pm 800A$	0 TO $\pm 2000A$	0 TO $\pm 1000A$					
0 TO $\pm 600A$	0 TO $\pm 1500A$											
0 TO $\pm 800A$	0 TO $\pm 2000A$											
0 TO $\pm 1000A$												
	<p><b>SERIES 909M4</b> ▶ <a href="#">Data Sheet</a></p> <p>CLAMP-ON; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER <math>\pm 15VDC</math>; RESPONSE 200<math>\mu</math>-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; METAL CASE; BARRIER SCREW OR CONNECTOR TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 150A</math></td> <td>0 TO <math>\pm 1000A</math></td> </tr> <tr> <td>0 TO <math>\pm 250A</math></td> <td>0 TO <math>\pm 1500A</math></td> </tr> <tr> <td>0 TO <math>\pm 500A</math></td> <td>0 TO <math>\pm 2000A</math></td> </tr> <tr> <td>0 TO <math>\pm 750A</math></td> <td>0 TO <math>\pm 2500A</math></td> </tr> </table>	0 TO $\pm 150A$	0 TO $\pm 1000A$	0 TO $\pm 250A$	0 TO $\pm 1500A$	0 TO $\pm 500A$	0 TO $\pm 2000A$	0 TO $\pm 750A$	0 TO $\pm 2500A$		
0 TO $\pm 150A$	0 TO $\pm 1000A$											
0 TO $\pm 250A$	0 TO $\pm 1500A$											
0 TO $\pm 500A$	0 TO $\pm 2000A$											
0 TO $\pm 750A$	0 TO $\pm 2500A$											
	<p><b>SERIES 9000</b> ▶ <a href="#">Data Sheet</a></p> <p>CLAMP-ON; OUTPUT 0 TO <math>\pm 5V</math>; ACCURACY 1%FS; POWER <math>\pm 15VDC</math>; RESPONSE 200<math>\mu</math>-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW OR CONNECTOR TERMINATIONS</p>	<p><b>CURRENT RANGES</b></p> <table> <tr> <td>0 TO <math>\pm 150A</math></td> <td>0 TO <math>\pm 1000A</math></td> </tr> <tr> <td>0 TO <math>\pm 250A</math></td> <td>0 TO <math>\pm 1500A</math></td> </tr> <tr> <td>0 TO <math>\pm 500A</math></td> <td>0 TO <math>\pm 2000A</math></td> </tr> <tr> <td>0 TO <math>\pm 750A</math></td> <td>0 TO <math>\pm 2500A</math></td> </tr> </table>	0 TO $\pm 150A$	0 TO $\pm 1000A$	0 TO $\pm 250A$	0 TO $\pm 1500A$	0 TO $\pm 500A$	0 TO $\pm 2000A$	0 TO $\pm 750A$	0 TO $\pm 2500A$		
0 TO $\pm 150A$	0 TO $\pm 1000A$											
0 TO $\pm 250A$	0 TO $\pm 1500A$											
0 TO $\pm 500A$	0 TO $\pm 2000A$											
0 TO $\pm 750A$	0 TO $\pm 2500A$											
	<p><b>SERIES S630</b> ▶ <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT; OUTPUT 0 TO <math>\pm 250mA</math>; ACCURACY 0.5%FS; POWER +24VDC; RESPONSE 1M-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BUS-BAR AVAILABLE; BARRIER SCREW TERMINATIONS</p>	<p><b>CURRENT RANGE</b> 0 TO <math>\pm 1000A</math></p> <p>OUTPUT TO INPUT RATIO: <math>\pm 250\mu A</math> PER AMP</p>										







	<p><b>SERIES 904B</b></p> <p>MIL GRADE; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; TEMPERATURE -55° TO +85°C; INPUT VIA IN-LINE CONNECTION; RESPONSE 50m-SEC; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +100μA</td> <td>0 TO +1MA</td> </tr> <tr> <td>0 TO +200μA</td> <td>0 TO +2MA</td> </tr> <tr> <td>0 TO +500μA</td> <td>0 TO +5MA</td> </tr> </table>	0 TO +100μA	0 TO +1MA	0 TO +200μA	0 TO +2MA	0 TO +500μA	0 TO +5MA						
0 TO +100μA	0 TO +1MA													
0 TO +200μA	0 TO +2MA													
0 TO +500μA	0 TO +5MA													
	<p><b>SERIES 903B</b></p> <p>MIL GRADE; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 50m-SEC; TEMPERATURE -55° TO +85°C; APERTURE 3/8 INCH DIA; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +5MA</td> <td>0 TO +100MA</td> <td>0 TO +1A</td> </tr> <tr> <td>0 TO +10MA</td> <td>0 TO +200MA</td> <td>0 TO +2A</td> </tr> <tr> <td>0 TO +20MA</td> <td>0 TO +500MA</td> <td>0 TO +5A</td> </tr> <tr> <td>0 TO +50MA</td> <td></td> <td></td> </tr> </table>	0 TO +5MA	0 TO +100MA	0 TO +1A	0 TO +10MA	0 TO +200MA	0 TO +2A	0 TO +20MA	0 TO +500MA	0 TO +5A	0 TO +50MA		
0 TO +5MA	0 TO +100MA	0 TO +1A												
0 TO +10MA	0 TO +200MA	0 TO +2A												
0 TO +20MA	0 TO +500MA	0 TO +5A												
0 TO +50MA														
	<p><b>SERIES S767</b></p> <p>SPACE FLIGHT; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +22 TO 36VDC; RESPONSE 50m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 1/2 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +10MA</td> <td>0 TO +200MA</td> </tr> <tr> <td>0 TO +20MA</td> <td>0 TO +250MA</td> </tr> <tr> <td>0 TO +50MA</td> <td>0 TO +500MA</td> </tr> <tr> <td>0 TO +100MA</td> <td>0 TO +1A</td> </tr> </table>	0 TO +10MA	0 TO +200MA	0 TO +20MA	0 TO +250MA	0 TO +50MA	0 TO +500MA	0 TO +100MA	0 TO +1A				
0 TO +10MA	0 TO +200MA													
0 TO +20MA	0 TO +250MA													
0 TO +50MA	0 TO +500MA													
0 TO +100MA	0 TO +1A													
	<p><b>SERIES 936</b></p> <p>HV GROUND FAULT; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 100m-SEC; TEMPERATURE -55° TO +85°C; APERTURE 3/4 INCH DIA; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +10MA</td> <td>0 TO +200MA</td> <td>0 TO +1A</td> </tr> <tr> <td>0 TO +20MA</td> <td>0 TO +250MA</td> <td>0 TO +2A</td> </tr> <tr> <td>0 TO +50MA</td> <td>0 TO +500MA</td> <td>0 TO +5A</td> </tr> <tr> <td>0 TO +100MA</td> <td></td> <td></td> </tr> </table>	0 TO +10MA	0 TO +200MA	0 TO +1A	0 TO +20MA	0 TO +250MA	0 TO +2A	0 TO +50MA	0 TO +500MA	0 TO +5A	0 TO +100MA		
0 TO +10MA	0 TO +200MA	0 TO +1A												
0 TO +20MA	0 TO +250MA	0 TO +2A												
0 TO +50MA	0 TO +500MA	0 TO +5A												
0 TO +100MA														
	<p><b>SERIES S218</b></p> <p>GROUND FAULT OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 50m-SEC; TEMPERATURE -55° TO +85°C; APERTURE 1+1/4 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +100MA</td> <td>0 TO +1A</td> </tr> <tr> <td>0 TO +200MA</td> <td>0 TO +2A</td> </tr> <tr> <td>0 TO +500MA</td> <td>0 TO +5A</td> </tr> </table>	0 TO +100MA	0 TO +1A	0 TO +200MA	0 TO +2A	0 TO +500MA	0 TO +5A						
0 TO +100MA	0 TO +1A													
0 TO +200MA	0 TO +2A													
0 TO +500MA	0 TO +5A													
	<p><b>SERIES S619</b></p> <p>SPACE FLIGHT; OUTPUT 0 TO +3.5V (ISOLATED); ACCURACY 2%FS; POWER +4.5 TO +5.5VDC; INPUT CURRENT BY IN-LINE CONNECTION; RESPONSE 1m-SEC; TEMPERATURE -55° TO +85°C; PCB MOUNT; SOLDER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +3.5A</td> <td>0 TO +10A</td> </tr> </table>	0 TO +3.5A	0 TO +10A										
0 TO +3.5A	0 TO +10A													
	<p><b>SERIES 950</b></p> <p>MIL GRADE; OUTPUT 0 TO +5V; ACCURACY 0.5%FS; POWER +24 TO 32VDC; RESPONSE 10m-SEC; TEMPERATURE -25° TO +85°C; APERTURE 3/8 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +10A</td> <td>0 TO +40A</td> </tr> <tr> <td>0 TO +20A</td> <td>0 TO +50A</td> </tr> <tr> <td>0 TO +30A</td> <td></td> </tr> </table>	0 TO +10A	0 TO +40A	0 TO +20A	0 TO +50A	0 TO +30A							
0 TO +10A	0 TO +40A													
0 TO +20A	0 TO +50A													
0 TO +30A														
	<p><b>SERIES 913B</b></p> <p>MIL GRADE; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 1m-SEC; TEMPERATURE -55° TO +85°C; APERTURE 3/4 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +10A</td> <td>0 TO +30A</td> <td>0 TO +50A</td> </tr> <tr> <td>0 TO +15A</td> <td>0 TO +35A</td> <td>0 TO +75A</td> </tr> <tr> <td>0 TO +20A</td> <td>0 TO +40A</td> <td>0 TO +100A</td> </tr> <tr> <td>0 TO +25A</td> <td></td> <td></td> </tr> </table>	0 TO +10A	0 TO +30A	0 TO +50A	0 TO +15A	0 TO +35A	0 TO +75A	0 TO +20A	0 TO +40A	0 TO +100A	0 TO +25A		
0 TO +10A	0 TO +30A	0 TO +50A												
0 TO +15A	0 TO +35A	0 TO +75A												
0 TO +20A	0 TO +40A	0 TO +100A												
0 TO +25A														
	<p><b>SERIES 913A</b></p> <p>MIL GRADE; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 1m-SEC; TEMPERATURE -55° TO +85°C; APERTURE 3/8 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO +10A</td> <td>0 TO +40A</td> </tr> <tr> <td>0 TO +20A</td> <td>0 TO +50A</td> </tr> <tr> <td>0 TO +25A</td> <td>0 TO +75A</td> </tr> <tr> <td>0 TO +30A</td> <td>0 TO +100A</td> </tr> </table>	0 TO +10A	0 TO +40A	0 TO +20A	0 TO +50A	0 TO +25A	0 TO +75A	0 TO +30A	0 TO +100A				
0 TO +10A	0 TO +40A													
0 TO +20A	0 TO +50A													
0 TO +25A	0 TO +75A													
0 TO +30A	0 TO +100A													

	<p><b>SERIES S770</b></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +12 TO 36VDC; RESPONSE 1m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; CHASSIS MOUNT; BARRIER SCREW TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +20A</td> <td>0 TO +60A</td> </tr> <tr> <td>0 TO +25A</td> <td>0 TO +70A</td> </tr> <tr> <td>0 TO +30A</td> <td>0 TO +100A</td> </tr> <tr> <td>0 TO +50A</td> <td></td> </tr> </table>	0 TO +20A	0 TO +60A	0 TO +25A	0 TO +70A	0 TO +30A	0 TO +100A	0 TO +50A					
0 TO +20A	0 TO +60A													
0 TO +25A	0 TO +70A													
0 TO +30A	0 TO +100A													
0 TO +50A														
	<p><b>SERIES 920</b></p> <p>CLAMP-ON; OUTPUT 4 TO +20mADC; ACCURACY 1%FS; LOOP POWER +18 TO 28VDC; RESPONSE 10m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 1.60 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +50A</td> <td>0 TO +100A</td> </tr> <tr> <td>0 TO +75A</td> <td>0 TO +125A</td> </tr> </table>	0 TO +50A	0 TO +100A	0 TO +75A	0 TO +125A								
0 TO +50A	0 TO +100A													
0 TO +75A	0 TO +125A													
	<p><b>SERIES S728B</b></p> <p>SPACE FLIGHT; OUTPUT 0 TO +5V; ACCURACY 0.3% TO 0.5%FS; POWER +24 TO 32VDC; RESPONSE 1μ-SEC; TEMPERATURE -55° TO +85°C; APERTURE 1/2 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER HEADER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +50A</td> <td>0 TO +250A</td> </tr> <tr> <td>0 TO +100A</td> <td>0 TO +300A</td> </tr> <tr> <td>0 TO +150A</td> <td>0 TO +400A</td> </tr> <tr> <td>0 TO +200A</td> <td></td> </tr> </table>	0 TO +50A	0 TO +250A	0 TO +100A	0 TO +300A	0 TO +150A	0 TO +400A	0 TO +200A					
0 TO +50A	0 TO +250A													
0 TO +100A	0 TO +300A													
0 TO +150A	0 TO +400A													
0 TO +200A														
	<p><b>SERIES 952</b></p> <p>MIL GRADE; OUTPUT 0 TO +5V; ACCURACY 0.3% TO 0.5%FS; POWER +24 TO 32VDC; RESPONSE 1μ-SEC; TEMPERATURE -55° TO +85°C; APERTURE 3/4 INCH DIA; METAL CASE; CHASSIS MOUNT; SOLDER HEADER TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +50A</td> <td>0 TO +250A</td> <td>0 TO +500A</td> </tr> <tr> <td>0 TO +100A</td> <td>0 TO +300A</td> <td>0 TO +600A</td> </tr> <tr> <td>0 TO +150A</td> <td>0 TO +400A</td> <td>0 TO +750A</td> </tr> <tr> <td>0 TO +200A</td> <td></td> <td></td> </tr> </table>	0 TO +50A	0 TO +250A	0 TO +500A	0 TO +100A	0 TO +300A	0 TO +600A	0 TO +150A	0 TO +400A	0 TO +750A	0 TO +200A		
0 TO +50A	0 TO +250A	0 TO +500A												
0 TO +100A	0 TO +300A	0 TO +600A												
0 TO +150A	0 TO +400A	0 TO +750A												
0 TO +200A														
	<p><b>SERIES S347</b></p> <p>CLAMP-ON; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 200μ-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; METAL CASE; BARRIER SCREW OR CONNECTOR TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +100A</td> <td>0 TO +300A</td> <td>0 TO +1500A</td> </tr> <tr> <td>0 TO +150A</td> <td>0 TO +500A</td> <td>0 TO +2000A</td> </tr> <tr> <td>0 TO +200A</td> <td>0 TO +750A</td> <td>0 TO +2500A</td> </tr> <tr> <td>0 TO +250A</td> <td>0 TO +1000A</td> <td></td> </tr> </table>	0 TO +100A	0 TO +300A	0 TO +1500A	0 TO +150A	0 TO +500A	0 TO +2000A	0 TO +200A	0 TO +750A	0 TO +2500A	0 TO +250A	0 TO +1000A	
0 TO +100A	0 TO +300A	0 TO +1500A												
0 TO +150A	0 TO +500A	0 TO +2000A												
0 TO +200A	0 TO +750A	0 TO +2500A												
0 TO +250A	0 TO +1000A													
	<p><b>SERIES 921</b></p> <p>CLAMP-ON; OUTPUT 4 TO +20mADC; ACCURACY 1%FS; LOOP POWER +18 TO 28VDC; RESPONSE 10m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 1.60 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +200A</td> <td>0 TO +400A</td> <td>0 TO +1000A</td> </tr> <tr> <td>0 TO +250A</td> <td>0 TO +500A</td> <td>0 TO +1500A</td> </tr> <tr> <td>0 TO +300A</td> <td>0 TO +750A</td> <td>0 TO +2000A</td> </tr> </table>	0 TO +200A	0 TO +400A	0 TO +1000A	0 TO +250A	0 TO +500A	0 TO +1500A	0 TO +300A	0 TO +750A	0 TO +2000A			
0 TO +200A	0 TO +400A	0 TO +1000A												
0 TO +250A	0 TO +500A	0 TO +1500A												
0 TO +300A	0 TO +750A	0 TO +2000A												
	<p><b>SERIES S966</b></p> <p>INDUSTRIAL GRADE OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +11 TO 32VDC; RESPONSE 200μ-SEC; TEMPERATURE -40° TO +85°C; APERTURE 2.20 INCH DIA; PLASTIC CASE; CONNECTOR TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +500A</td> <td>0 TO +1500A</td> <td>0 TO +3000A</td> </tr> <tr> <td>0 TO +750A</td> <td>0 TO +2000A</td> <td>0 TO +3500A</td> </tr> <tr> <td>0 TO +1000A</td> <td>0 TO +2500A</td> <td>0 TO +4000A</td> </tr> <tr> <td></td> <td></td> <td>0 TO +5000A</td> </tr> </table>	0 TO +500A	0 TO +1500A	0 TO +3000A	0 TO +750A	0 TO +2000A	0 TO +3500A	0 TO +1000A	0 TO +2500A	0 TO +4000A			0 TO +5000A
0 TO +500A	0 TO +1500A	0 TO +3000A												
0 TO +750A	0 TO +2000A	0 TO +3500A												
0 TO +1000A	0 TO +2500A	0 TO +4000A												
		0 TO +5000A												
	<p><b>SERIES S444</b></p> <p>CLAMP-ON; OUTPUT 0 TO +5V; ACCURACY 1%FS; POWER +24 TO 32VDC; RESPONSE 200μ-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW OR CONNECTOR TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +200A</td> <td>0 TO +500A</td> <td>0 TO +1500A</td> </tr> <tr> <td>0 TO +225A</td> <td>0 TO +750A</td> <td>0 TO +2000A</td> </tr> <tr> <td>0 TO +250A</td> <td>0 TO +1000A</td> <td>0 TO +2500A</td> </tr> <tr> <td>0 TO +300A</td> <td></td> <td></td> </tr> </table>	0 TO +200A	0 TO +500A	0 TO +1500A	0 TO +225A	0 TO +750A	0 TO +2000A	0 TO +250A	0 TO +1000A	0 TO +2500A	0 TO +300A		
0 TO +200A	0 TO +500A	0 TO +1500A												
0 TO +225A	0 TO +750A	0 TO +2000A												
0 TO +250A	0 TO +1000A	0 TO +2500A												
0 TO +300A														
	<p><b>SERIES S465</b></p> <p>RAIL TRANSIT CLAMP-ON; OUTPUT 4 TO 20mA; ACCURACY 1%FS; POWER +16 TO 26VDC; RESPONSE 200μ-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW OR CONNECTOR TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +150A</td> <td>0 TO +1000A</td> </tr> <tr> <td>0 TO +250A</td> <td>0 TO +1500A</td> </tr> <tr> <td>0 TO +500A</td> <td>0 TO +2000A</td> </tr> <tr> <td>0 TO +750A</td> <td>0 TO +2500A</td> </tr> </table>	0 TO +150A	0 TO +1000A	0 TO +250A	0 TO +1500A	0 TO +500A	0 TO +2000A	0 TO +750A	0 TO +2500A				
0 TO +150A	0 TO +1000A													
0 TO +250A	0 TO +1500A													
0 TO +500A	0 TO +2000A													
0 TO +750A	0 TO +2500A													
	<p><b>SERIES S646</b></p> <p>RAIL TRANSIT CLAMP-ON; OUTPUT 0 TO +6V; ACCURACY 2%FS; POWER +15VDC; RESPONSE 200μ-SEC; TEMPERATURE -30° TO +60°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p> <p><a href="#">Data Sheet</a></p>	<p><b>DC CURRENT RANGES</b></p> <table> <tr> <td>0 TO +1000A</td> </tr> </table>	0 TO +1000A											
0 TO +1000A														

	<p><b>SERIES 901B</b>  <a href="#">Data Sheet</a></p> <p>GROUND FAULT; OUTPUT SOLID-STATE-SWITCH AND 0 TO 5VDC; ACCURACY 1%FS; POWER +21 TO +27VDC; RESPONSE 50M-SEC; TEMPERATURE -20° TO +70°C; APERTURE 3/4 INCH DIA; METAL CASE; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 TO +20MA      0 TO +500MA            0 TO +50MA      0 TO +1A            0 TO +100MA      0 TO +2A            0 TO + 250MA      0 TO +5A</p>
	<p><b>SERIES S204</b>  <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT SPDT RELAY; ACCURACY 4% OF SET POINT; POWER +22.8 TO +30.4VDC; RESPONSE 3M-SEC; TEMP. -20° TO +70°C; APERTURE 3/8 INCH DIA; METAL CASE; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 TO +100MA      0 TO +1.2A            0 TO +150MA      0 TO +2A            0 TO +350MA      0 TO +3A            0 TO +550MA      0 TO +5.75A</p>
	<p><b>SERIES S58</b>  <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT SOLID-STATE-SWITCH; AUTOMATIC RESET; POWER +22.8 TO +30.4VDC; RESPONSE 1M-SEC; TEMPERATURE 0° TO +70°C; APERTURE 3/8 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 TO +15ADC</p> <p>SWITCH TRIPS @ 60MADC ±20%</p>
	<p><b>SERIES S754</b>  <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT; OUTPUT SOLID-STATE-RELAY; PUSHBUTTON RESET; RESPONSE 100M-SEC; POWER +25 TO +45VDC; TEMPERATURE -40° TO +50°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 TO +20ADC</p> <p>ADJUSTABLE TRIP CURRENT 500MA TO 1ADC</p>
	<p><b>SERIES S201</b>  <a href="#">Data Sheet</a></p> <p>AIRCRAFT DO-160; OUTPUT SPST RELAY; AUTOMATIC RESET; POWER +24 TO +32VDC; RESPONSE 200M-SEC; TEMP. -55° TO +70°C; APERTURE 3/8 INCH DIA; METAL CASE; CONNECTOR TERMINATIONS; DO-160 ENVIRONMENTAL REQUIREMENTS</p>	<p><b>DC CURRENT RANGES</b>            0 TO +100ADC</p> <p>RELAY TRIPS @ +1ADC ±15%</p>
	<p><b>SERIES S680</b>  <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT; OUTPUT SOLID-STATE-RELAY; AUTOMATIC RESET; POWER +25 TO +45VDC; RESPONSE 1M-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; AVAILABLE WITH BUS-BAR; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 to +1000A<sub>dc</sub></p> <p>RELAY TRIPS @ ±3A<sub>dc</sub> ±10%</p>
	<p><b>SERIES S629</b>  <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT; OUTPUT SPST RELAY (10A CONTACTS); AUTOMATIC RESET; RESPONSE 50M-SEC; TEMP -25° TO +75°C; POWER +25 TO +45VDC; APERTURE 1+1/2 INCH DIA; BUS-BAR AVAILABLE; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 to +1000A<sub>dc</sub></p> <p>RELAY TRIPS @ ±45A<sub>dc</sub> ±0.5A<sub>dc</sub></p>
	<p><b>SERIES S623</b>  <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT GROUND FAULT; OUTPUT SPST RELAY; AUTOMATIC RESET; RESPONSE 50M-SEC; POWER +25 TO +45VDC; TEMP -25° TO +75°C; APERTURE 1+1/2 INCH DIA; DUAL BUS-BAR AVAILABLE; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>DC CURRENT RANGES</b>            0 to +1600A<sub>dc</sub></p> <p>RELAY TRIP ADJUSTMENT RANGE:</p>

	<p><b>SERIES 1055L</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 4 TO 20mA; ACCURACY 0.5%FS; TWO WIRE LOOP POWER +7 TO +35VDC; FREQUENCY 50-60HZ; RESPONSE 100m-SEC; TEMP. -20° TO +85°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 50MA</td> <td>0 TO 250MA</td> </tr> <tr> <td>0 TO 100MA</td> <td>0 TO 500MA</td> </tr> <tr> <td>0 TO 200MA</td> <td>0 TO 1A</td> </tr> </table>	0 TO 50MA	0 TO 250MA	0 TO 100MA	0 TO 500MA	0 TO 200MA	0 TO 1A									
0 TO 50MA	0 TO 250MA																
0 TO 100MA	0 TO 500MA																
0 TO 200MA	0 TO 1A																
	<p><b>SERIES S383L</b> ▶ <a href="#">Data Sheet</a></p> <p>PROCESS CONTROL; OUTPUT 4 TO 20mA; ACCURACY 0.5%FS; TWO WIRE LOOP POWER +7 TO +35VDC; FREQUENCY 50-60HZ; RESPONSE 100m-SEC; TEMP. -40° TO +85°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 50MA</td> <td>0 TO 250MA</td> </tr> <tr> <td>0 TO 100MA</td> <td>0 TO 500MA</td> </tr> <tr> <td>0 TO 200MA</td> <td>0 TO 1A</td> </tr> </table>	0 TO 50MA	0 TO 250MA	0 TO 100MA	0 TO 500MA	0 TO 200MA	0 TO 1A									
0 TO 50MA	0 TO 250MA																
0 TO 100MA	0 TO 500MA																
0 TO 200MA	0 TO 1A																
	<p><b>SERIES 1002M1</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; POWER +24 TO +32VDC; FREQUENCY 375-475Hz (OTHERS AVAILABLE); RESPONSE 10m-SEC; TEMPERATURE -55° TO +85°C; APERTURE 3/4 INCH DIA; SOLDER, CONNECTOR OR BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 250MA</td> <td>0 TO 20A</td> <td>0 TO 100A</td> </tr> <tr> <td>0 TO 500MA</td> <td>0 TO 25A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 1A</td> <td>0 TO 50A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 65A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 10A</td> <td></td> <td></td> </tr> </table>	0 TO 250MA	0 TO 20A	0 TO 100A	0 TO 500MA	0 TO 25A	0 TO 150A	0 TO 1A	0 TO 50A	0 TO 200A	0 TO 5A	0 TO 65A	0 TO 250A	0 TO 10A		
0 TO 250MA	0 TO 20A	0 TO 100A															
0 TO 500MA	0 TO 25A	0 TO 150A															
0 TO 1A	0 TO 50A	0 TO 200A															
0 TO 5A	0 TO 65A	0 TO 250A															
0 TO 10A																	
	<p><b>SERIES S402</b> ▶ <a href="#">Data Sheet</a></p> <p>RMS RESPONDING; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; POWER +24 TO +32VDC; FREQUENCY 57-63Hz (OTHERS AVAILABLE); RESPONSE 100m-SEC; TEMPERATURE 0° TO 70°C; APERTURE 3/4 INCH DIA; METAL CASE; SOLDER, CONNECTOR OR BARRIER TERMINALS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 250MA</td> <td>0 TO 5A</td> <td>0 TO 100A</td> </tr> <tr> <td>0 TO 500MA</td> <td>0 TO 10A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 1A</td> <td>0 TO 20A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 2A</td> <td>0 TO 50A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 3A</td> <td></td> <td></td> </tr> </table>	0 TO 250MA	0 TO 5A	0 TO 100A	0 TO 500MA	0 TO 10A	0 TO 150A	0 TO 1A	0 TO 20A	0 TO 200A	0 TO 2A	0 TO 50A	0 TO 250A	0 TO 3A		
0 TO 250MA	0 TO 5A	0 TO 100A															
0 TO 500MA	0 TO 10A	0 TO 150A															
0 TO 1A	0 TO 20A	0 TO 200A															
0 TO 2A	0 TO 50A	0 TO 250A															
0 TO 3A																	
	<p><b>SERIES C</b> ▶ <a href="#">Data Sheet</a></p> <p>AVERAGE RESPONDING; OUTPUT 0 TO 1mAdc; ACCURACY 0.25%FS; POWERED BY INPUT; FREQUENCY 47-1000Hz; RESPONSE 400m-SEC; TEMPERATURE -20° TO +70°C; INPUT BY IN-LINE CONNECTION; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 1A</td> <td>0 TO 10A</td> </tr> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> </tr> <tr> <td>0 TO 5A</td> <td></td> </tr> </table>	0 TO 1A	0 TO 10A	0 TO 2A	0 TO 20A	0 TO 5A										
0 TO 1A	0 TO 10A																
0 TO 2A	0 TO 20A																
0 TO 5A																	
	<p><b>SERIES CX</b> ▶ <a href="#">Data Sheet</a></p> <p>AVERAGE RESPONDING; OUTPUT 4 TO 20mAdc; ACCURACY 0.25%FS; LOOP-POWER 10 TO 35VDC; FREQUENCY 47-1000Hz; RESPONSE 400m-SEC; TEMPERATURE -20° TO +70°C; INPUT BY IN-LINE CONNECTION; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 1A</td> <td>0 TO 10A</td> </tr> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> </tr> <tr> <td>0 TO 5A</td> <td></td> </tr> </table>	0 TO 1A	0 TO 10A	0 TO 2A	0 TO 20A	0 TO 5A										
0 TO 1A	0 TO 10A																
0 TO 2A	0 TO 20A																
0 TO 5A																	
	<p><b>SERIES 1003AM1</b> ▶ <a href="#">Data Sheet</a></p> <p>PROCESS OUTPUT 0 TO 5VDC; ACCURACY 1%FS; FREQUENCY 57-63Hz (OTHERS AVAILABLE); POWERED BY INPUT; RESPONSE 150m - SEC; TEMPERATURE -20° TO +70°C; APERTURE 3/8 INCH DIA; METAL CASE; BARRIER TERMINALS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> <td>0 TO 50A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 25A</td> <td>0 TO 60A</td> </tr> <tr> <td>0 TO 7A</td> <td>0 TO 30A</td> <td>0 TO 75A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 40A</td> <td>0 TO 100A</td> </tr> <tr> <td>0 TO 15A</td> <td></td> <td></td> </tr> </table>	0 TO 2A	0 TO 20A	0 TO 50A	0 TO 5A	0 TO 25A	0 TO 60A	0 TO 7A	0 TO 30A	0 TO 75A	0 TO 10A	0 TO 40A	0 TO 100A	0 TO 15A		
0 TO 2A	0 TO 20A	0 TO 50A															
0 TO 5A	0 TO 25A	0 TO 60A															
0 TO 7A	0 TO 30A	0 TO 75A															
0 TO 10A	0 TO 40A	0 TO 100A															
0 TO 15A																	
	<p><b>SERIES 1004</b> ▶ <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO 5VDC; ACCURACY 1%FS; FREQUENCY 375 TO 475Hz; RESPONSE 150m-SEC; TEMPERATURE -55° TO +85°C; POWERED BY INPUT; APERTURE 3/8 OR 3/4 INCH DIA; METAL CASE; SOLDER, CONNECTOR OR BARRIER TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 2A</td> <td>0 TO 50A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 100A</td> <td>0 TO 300A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 150A</td> <td>0 TO 350A</td> </tr> <tr> <td>0 TO 20A</td> <td>0 TO 200A</td> <td>0 TO 400A</td> </tr> </table>	0 TO 2A	0 TO 50A	0 TO 250A	0 TO 5A	0 TO 100A	0 TO 300A	0 TO 10A	0 TO 150A	0 TO 350A	0 TO 20A	0 TO 200A	0 TO 400A			
0 TO 2A	0 TO 50A	0 TO 250A															
0 TO 5A	0 TO 100A	0 TO 300A															
0 TO 10A	0 TO 150A	0 TO 350A															
0 TO 20A	0 TO 200A	0 TO 400A															
	<p><b>SERIES 1005</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO 5VDC; ACCURACY 1-2%FS; FREQUENCY 50 TO 60Hz; RESPONSE 80m-SEC; TEMPERATURE -20° TO +70°C; POWERED BY INPUT; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 2A</td> <td>0 TO 30A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 50A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 75A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 20A</td> <td>0 TO 100A</td> <td>0 TO 300A</td> </tr> </table>	0 TO 2A	0 TO 30A	0 TO 150A	0 TO 5A	0 TO 50A	0 TO 200A	0 TO 10A	0 TO 75A	0 TO 250A	0 TO 20A	0 TO 100A	0 TO 300A			
0 TO 2A	0 TO 30A	0 TO 150A															
0 TO 5A	0 TO 50A	0 TO 200A															
0 TO 10A	0 TO 75A	0 TO 250A															
0 TO 20A	0 TO 100A	0 TO 300A															
	<p><b>SERIES 1055</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 4 TO 20mA; ACCURACY 0.5%FS; TWO WIRE LOOP POWER +7 TO +35VDC; FREQUENCY 50-60Hz; RESPONSE 100m-SEC; TEMPERATURE -20° TO +85°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table> <tr> <td>0 TO 2A</td> <td>0 TO 30A</td> <td>0 TO 100A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 40A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 50A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 20A</td> <td>0 TO 75A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 25A</td> <td></td> <td></td> </tr> </table>	0 TO 2A	0 TO 30A	0 TO 100A	0 TO 5A	0 TO 40A	0 TO 150A	0 TO 10A	0 TO 50A	0 TO 200A	0 TO 20A	0 TO 75A	0 TO 250A	0 TO 25A		
0 TO 2A	0 TO 30A	0 TO 100A															
0 TO 5A	0 TO 40A	0 TO 150A															
0 TO 10A	0 TO 50A	0 TO 200A															
0 TO 20A	0 TO 75A	0 TO 250A															
0 TO 25A																	

	<p><b>SERIES S383</b>  <a href="#">Data Sheet</a></p> <p>PROCESS CONTROL; OUTPUT 4 TO 20mA; ACCURACY 0.5%FS; TWO WIRE LOOP POWER +7 TO +35VDC; FREQUENCY 50-60HZ; RESPONSE 100m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 2A</td> <td>0 TO 30A</td> <td>0 TO 100A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 40A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 50A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 20A</td> <td>0 TO 75A</td> <td>0 TO 250A</td> </tr> </table>	0 TO 2A	0 TO 30A	0 TO 100A	0 TO 5A	0 TO 40A	0 TO 150A	0 TO 10A	0 TO 50A	0 TO 200A	0 TO 20A	0 TO 75A	0 TO 250A				
0 TO 2A	0 TO 30A	0 TO 100A																
0 TO 5A	0 TO 40A	0 TO 150A																
0 TO 10A	0 TO 50A	0 TO 200A																
0 TO 20A	0 TO 75A	0 TO 250A																
	<p><b>SERIES 1070</b>  <a href="#">Data Sheet</a></p> <p>AC RMS; OUTPUT 4 TO 20mA; ACCURACY 0.25%FS; TWO WIRE LOOP POWER +12 TO +32VDC; FREQUENCY 20-2KHZ; RESPONSE 300m-SEC; TEMP -40° TO +85°C; APERTURE 3/4 INCH; PLASTIC CASE; BARRIER SCREW, CONNECTOR OR SUB-D TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> <td>0 TO 50A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 25A</td> <td>0 TO 75A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 30A</td> <td>0 TO 100A</td> <td></td> </tr> <tr> <td>0 TO 15A</td> <td>0 TO 40A</td> <td>0 TO 150A</td> <td></td> </tr> </table>	0 TO 2A	0 TO 20A	0 TO 50A	0 TO 200A	0 TO 5A	0 TO 25A	0 TO 75A	0 TO 250A	0 TO 10A	0 TO 30A	0 TO 100A		0 TO 15A	0 TO 40A	0 TO 150A	
0 TO 2A	0 TO 20A	0 TO 50A	0 TO 200A															
0 TO 5A	0 TO 25A	0 TO 75A	0 TO 250A															
0 TO 10A	0 TO 30A	0 TO 100A																
0 TO 15A	0 TO 40A	0 TO 150A																
	<p><b>SERIES 1006</b>  <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; FREQUENCY 50 TO 60HZ; RESPONSE 130m-SEC; TEMPERATURE -20° TO +70°C; POWERED BY INPUT; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 5A</td> <td>0 TO 75A</td> <td>0 TO 500A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 100A</td> <td>0 TO 600A</td> </tr> <tr> <td>0 TO 25A</td> <td>0 TO 150A</td> <td>0 TO 800A</td> </tr> <tr> <td>0 TO 30A</td> <td>0 TO 250A</td> <td>0 TO 1000A</td> </tr> <tr> <td>0 TO 50A</td> <td>0 TO 400A</td> <td></td> </tr> </table>	0 TO 5A	0 TO 75A	0 TO 500A	0 TO 10A	0 TO 100A	0 TO 600A	0 TO 25A	0 TO 150A	0 TO 800A	0 TO 30A	0 TO 250A	0 TO 1000A	0 TO 50A	0 TO 400A		
0 TO 5A	0 TO 75A	0 TO 500A																
0 TO 10A	0 TO 100A	0 TO 600A																
0 TO 25A	0 TO 150A	0 TO 800A																
0 TO 30A	0 TO 250A	0 TO 1000A																
0 TO 50A	0 TO 400A																	
	<p><b>SERIES 1006X</b>  <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 4 TO 20mADC; ACCURACY 0.5%FS; FREQUENCY 50 TO 60HZ; LOOP POWER +5 TO +35VDC; RESPONSE 100m-SEC; TEMPERATURE -20° TO +70°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 5A</td> <td>0 TO 100A</td> <td>0 TO 500A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 150A</td> <td>0 TO 800A</td> </tr> <tr> <td>0 TO 25A</td> <td>0 TO 200A</td> <td>0 TO 1000A</td> </tr> <tr> <td>0 TO 50A</td> <td>0 TO 300A</td> <td>0 TO 1200A</td> </tr> <tr> <td>0 TO 75A</td> <td>0 TO 400A</td> <td></td> </tr> </table>	0 TO 5A	0 TO 100A	0 TO 500A	0 TO 10A	0 TO 150A	0 TO 800A	0 TO 25A	0 TO 200A	0 TO 1000A	0 TO 50A	0 TO 300A	0 TO 1200A	0 TO 75A	0 TO 400A		
0 TO 5A	0 TO 100A	0 TO 500A																
0 TO 10A	0 TO 150A	0 TO 800A																
0 TO 25A	0 TO 200A	0 TO 1000A																
0 TO 50A	0 TO 300A	0 TO 1200A																
0 TO 75A	0 TO 400A																	
	<p><b>SERIES S714</b>  <a href="#">Data Sheet</a></p> <p>RMS RESPONDING; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; FREQ. 360 TO 440HZ; POWER +14 TO +32VDC; RESPONSE 75m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 1+3/8 INCH DIA; METAL CASE; CONNECTOR OR BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 5A</td> <td>0 TO 75A</td> <td>0 TO 300A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 100A</td> <td>0 TO 400A</td> </tr> <tr> <td>0 TO 25A</td> <td>0 TO 150A</td> <td>0 TO 500A</td> </tr> <tr> <td>0 TO 50A</td> <td>0 TO 200A</td> <td>0 TO 600A</td> </tr> </table>	0 TO 5A	0 TO 75A	0 TO 300A	0 TO 10A	0 TO 100A	0 TO 400A	0 TO 25A	0 TO 150A	0 TO 500A	0 TO 50A	0 TO 200A	0 TO 600A				
0 TO 5A	0 TO 75A	0 TO 300A																
0 TO 10A	0 TO 100A	0 TO 400A																
0 TO 25A	0 TO 150A	0 TO 500A																
0 TO 50A	0 TO 200A	0 TO 600A																
	<p><b>SERIES S786</b>  <a href="#">Data Sheet</a></p> <p>RMS RESPONDING; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; FREQUENCY 60HZ; POWER +14 TO +32VDC; RESPONSE 75m-SEC; TEMPERATURE -40° TO +85°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 5A</td> <td>0 TO 75A</td> <td>0 TO 400A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 100A</td> <td>0 TO 500A</td> </tr> <tr> <td>0 TO 20A</td> <td>0 TO 150A</td> <td>0 TO 600A</td> </tr> <tr> <td>0 TO 25A</td> <td>0 TO 200A</td> <td>0 TO 800A</td> </tr> <tr> <td>0 TO 50A</td> <td>0 TO 300A</td> <td>0 TO 1000A</td> </tr> </table>	0 TO 5A	0 TO 75A	0 TO 400A	0 TO 10A	0 TO 100A	0 TO 500A	0 TO 20A	0 TO 150A	0 TO 600A	0 TO 25A	0 TO 200A	0 TO 800A	0 TO 50A	0 TO 300A	0 TO 1000A	
0 TO 5A	0 TO 75A	0 TO 400A																
0 TO 10A	0 TO 100A	0 TO 500A																
0 TO 20A	0 TO 150A	0 TO 600A																
0 TO 25A	0 TO 200A	0 TO 800A																
0 TO 50A	0 TO 300A	0 TO 1000A																
	<p><b>SERIES 1003AM2</b>  <a href="#">Data Sheet</a></p> <p>AVG RESPONDING; OUTPUT 0 TO 5VDC; ACCURACY 1%FS; FREQUENCY 57-63HZ (OTHERS AVAILABLE); POWERED BY INPUT; RESPONSE 150m-SEC; TEMPERATURE -20° TO +70°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 10A</td> <td>0 TO 50A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 15A</td> <td>0 TO 75A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 20A</td> <td>0 TO 100A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 25A</td> <td>0 TO 125A</td> <td>0 TO 300A</td> </tr> <tr> <td>0 TO 30A</td> <td></td> <td></td> </tr> </table>	0 TO 10A	0 TO 50A	0 TO 150A	0 TO 15A	0 TO 75A	0 TO 200A	0 TO 20A	0 TO 100A	0 TO 250A	0 TO 25A	0 TO 125A	0 TO 300A	0 TO 30A			
0 TO 10A	0 TO 50A	0 TO 150A																
0 TO 15A	0 TO 75A	0 TO 200A																
0 TO 20A	0 TO 100A	0 TO 250A																
0 TO 25A	0 TO 125A	0 TO 300A																
0 TO 30A																		
	<p><b>SERIES 1001</b>  <a href="#">Data Sheet</a></p> <p>CLAMP-ON RMS RESPONDING; OUTPUT 0 TO 5VDC; ACCURACY 1%FS; FREQUENCY DC TO 480HZ; POWER +24 TO +32VDC; RESPONSE 100m-SEC; TEMPERATURE -25° TO +75°C; APERTURE 1+1/2 INCH DIA; METAL CASE; CONNECTOR OR BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 100A</td> <td>0 TO 750A</td> <td>0 TO 2000A</td> </tr> <tr> <td>0 TO 150A</td> <td>0 TO 1000A</td> <td>0 TO 2500A</td> </tr> <tr> <td>0 TO 250A</td> <td>0 TO 1500A</td> <td>0 TO 3000A</td> </tr> <tr> <td>0 TO 500A</td> <td></td> <td></td> </tr> </table>	0 TO 100A	0 TO 750A	0 TO 2000A	0 TO 150A	0 TO 1000A	0 TO 2500A	0 TO 250A	0 TO 1500A	0 TO 3000A	0 TO 500A						
0 TO 100A	0 TO 750A	0 TO 2000A																
0 TO 150A	0 TO 1000A	0 TO 2500A																
0 TO 250A	0 TO 1500A	0 TO 3000A																
0 TO 500A																		
	<p><b>SERIES S461</b>  <a href="#">Data Sheet</a></p> <p>CLAMP-ON RMS RESPONDING; OUTPUT 0 TO 5VDC; ACCURACY 1%FS; FREQUENCY DC TO 480HZ; POWER +24 TO +32VDC; RESPONSE 100m-SEC; TEMPERATURE -25° TO +71°C; APERTURE 1+1/2 INCH DIA; PLASTIC CASE; CONNECTOR OR BARRIER SCREW TERMINALS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 100A</td> <td>0 TO 750A</td> <td>0 TO 2000A</td> </tr> <tr> <td>0 TO 150A</td> <td>0 TO 1000A</td> <td>0 TO 2500A</td> </tr> <tr> <td>0 TO 250A</td> <td>0 TO 1500A</td> <td>0 TO 3000A</td> </tr> <tr> <td>0 TO 500A</td> <td></td> <td></td> </tr> </table>	0 TO 100A	0 TO 750A	0 TO 2000A	0 TO 150A	0 TO 1000A	0 TO 2500A	0 TO 250A	0 TO 1500A	0 TO 3000A	0 TO 500A						
0 TO 100A	0 TO 750A	0 TO 2000A																
0 TO 150A	0 TO 1000A	0 TO 2500A																
0 TO 250A	0 TO 1500A	0 TO 3000A																
0 TO 500A																		

	<p><b>SERIES 870</b> ▶ <a href="#">Data Sheet</a></p> <p>HEAVY INDUSTRIAL; OUTPUT SPDT-RELAY (10A CONTACTS); AUTO RESET; ADJUSTABLE (20% TO 100%); POWER 115VAC; FREQUENCY 47-63HZ; TEMPERATURE -20° TO +71°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 1A</td> <td>0 TO 15A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 50A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 100A</td> <td>0 TO 300A</td> </tr> </table>	0 TO 1A	0 TO 15A	0 TO 150A	0 TO 2A	0 TO 20A	0 TO 200A	0 TO 5A	0 TO 50A	0 TO 250A	0 TO 10A	0 TO 100A	0 TO 300A
0 TO 1A	0 TO 15A	0 TO 150A												
0 TO 2A	0 TO 20A	0 TO 200A												
0 TO 5A	0 TO 50A	0 TO 250A												
0 TO 10A	0 TO 100A	0 TO 300A												
	<p><b>SERIES S871</b> ▶ <a href="#">Data Sheet</a></p> <p>WIDE FREQUENCY; OUTPUT SPDT-RELAY (10A CONTACTS); AUTO RESET; ADJUSTABLE (20% TO 100%); POWER 115VAC; FREQUENCY 47-400HZ; TEMPERATURE -20° TO +71°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 1A</td> <td>0 TO 15A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 50A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 100A</td> <td>0 TO 300A</td> </tr> </table>	0 TO 1A	0 TO 15A	0 TO 150A	0 TO 2A	0 TO 20A	0 TO 200A	0 TO 5A	0 TO 50A	0 TO 250A	0 TO 10A	0 TO 100A	0 TO 300A
0 TO 1A	0 TO 15A	0 TO 150A												
0 TO 2A	0 TO 20A	0 TO 200A												
0 TO 5A	0 TO 50A	0 TO 250A												
0 TO 10A	0 TO 100A	0 TO 300A												
	<p><b>SERIES 882</b> ▶ <a href="#">Data Sheet</a></p> <p>CURRENT CONTROLLER; OUTPUT SPDT RELAY (2A CONTACTS); AUTO RESET; ADJUSTABLE (20% TO 100%); POWER 115VAC; FREQUENCY 50-400HZ; TEMPERATURE -20° TO +71°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 1A</td> <td>0 TO 15A</td> <td>0 TO 150A</td> </tr> <tr> <td>0 TO 2A</td> <td>0 TO 20A</td> <td>0 TO 200A</td> </tr> <tr> <td>0 TO 5A</td> <td>0 TO 50A</td> <td>0 TO 250A</td> </tr> <tr> <td>0 TO 10A</td> <td>0 TO 100A</td> <td>0 TO 300A</td> </tr> </table>	0 TO 1A	0 TO 15A	0 TO 150A	0 TO 2A	0 TO 20A	0 TO 200A	0 TO 5A	0 TO 50A	0 TO 250A	0 TO 10A	0 TO 100A	0 TO 300A
0 TO 1A	0 TO 15A	0 TO 150A												
0 TO 2A	0 TO 20A	0 TO 200A												
0 TO 5A	0 TO 50A	0 TO 250A												
0 TO 10A	0 TO 100A	0 TO 300A												
	<p><b>SERIES 881</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT SPDT-RELAY (2A CONTACTS); AUTOMATIC RESET; ADJUSTABLE TRIP POINT; POWER 115VAC; FREQUENCY 50-400HZ; TEMPERATURE -20° TO +70°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 12A.....</td> <td>(TRIP ADJ 2-12A)</td> </tr> <tr> <td>0 TO 50A.....</td> <td>(TRIP ADJ 8-50A)</td> </tr> <tr> <td>0 TO 120A.....</td> <td>(TRIP ADJ 40-120A)</td> </tr> <tr> <td>0 TO 250A.....</td> <td>(TRIP ADJ 100-250A)</td> </tr> </table>	0 TO 12A.....	(TRIP ADJ 2-12A)	0 TO 50A.....	(TRIP ADJ 8-50A)	0 TO 120A.....	(TRIP ADJ 40-120A)	0 TO 250A.....	(TRIP ADJ 100-250A)				
0 TO 12A.....	(TRIP ADJ 2-12A)													
0 TO 50A.....	(TRIP ADJ 8-50A)													
0 TO 120A.....	(TRIP ADJ 40-120A)													
0 TO 250A.....	(TRIP ADJ 100-250A)													
	<p><b>SERIES 880B</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT SOLID STATE SWITCH; AUTOMATIC RESET; POWERED BY INPUT; ADJUSTABLE TRIP POINT; FREQUENCY 50-400HZ; TEMPERATURE -20° TO +70°C; APERTURE 3/4 INCH DIA; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC CURRENT RANGES</b></p> <table border="0"> <tr> <td>0 TO 12A.....</td> <td>(TRIP ADJ 2-12A)</td> </tr> <tr> <td>0 TO 50A.....</td> <td>(TRIP ADJ 8-50A)</td> </tr> <tr> <td>0 TO 120A.....</td> <td>(TRIP ADJ 40-120A)</td> </tr> <tr> <td>0 TO 250A.....</td> <td>(TRIP ADJ 100-250A)</td> </tr> </table>	0 TO 12A.....	(TRIP ADJ 2-12A)	0 TO 50A.....	(TRIP ADJ 8-50A)	0 TO 120A.....	(TRIP ADJ 40-120A)	0 TO 250A.....	(TRIP ADJ 100-250A)				
0 TO 12A.....	(TRIP ADJ 2-12A)													
0 TO 50A.....	(TRIP ADJ 8-50A)													
0 TO 120A.....	(TRIP ADJ 40-120A)													
0 TO 250A.....	(TRIP ADJ 100-250A)													
	<p><b>SERIES S212</b> ▶ <a href="#">Data Sheet</a></p> <p>AIRCRAFT DO-160; OUTPUT SPDT-RELAY; AUTOMATIC RESET; POWER +24 TO +32VDC; RESPONSE 200M-SEC; TEMPERATURE -55° TO +70°C; APERTURE 3/8 INCH DIA; METAL CASE; CONNECTOR TERMINATIONS; DO-160 ENVIRONMENTAL REQUIREMENTS</p>	<p><b>AC CURRENT RANGES</b></p> <p>0 TO 75A (360-440Hz) RELAY TRIPS @ 0.5AAC ±0.75AAC</p>												

DATA SHEETS AT  
[www.a-a-c.com](http://www.a-a-c.com)

### AC VOLTAGE TRANSDUCERS

FIVE MODELS IN ORDER OF VOLTAGE RANGE

PAGE  
10 OF 13



	<p><b>SERIES 108</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; RESPONSE 300m-SEC; POWERED BY INPUT; FREQUENCY 57-63Hz (400Hz AVAILABLE); TEMPERATURE -20° TO +70°C; METAL CASE; BARRIER SCREW TERMINALS OR OPTIONAL CONNECTOR</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>0 TO 50V</td> <td>0 TO 300V</td> </tr> <tr> <td>0 TO 130V</td> <td>0 TO 500V</td> </tr> <tr> <td>0 TO 150V</td> <td>0 TO 600V</td> </tr> <tr> <td>0 TO 270V</td> <td></td> </tr> </table>	0 TO 50V	0 TO 300V	0 TO 130V	0 TO 500V	0 TO 150V	0 TO 600V	0 TO 270V	
0 TO 50V	0 TO 300V									
0 TO 130V	0 TO 500V									
0 TO 150V	0 TO 600V									
0 TO 270V										
	<p><b>SERIES 108X</b> ▶ <a href="#">Data Sheet</a></p> <p>PROCESS CONTROL; OUTPUT 4 TO 20mADC; ACCURACY 0.5%FS; RESPONSE 300m-SEC; LOOP POWER +10 TO +35VDC; FREQUENCY 57-63Hz (400Hz AVAILABLE); TEMPERATURE -20° TO +70°C; METAL CASE; BARRIER SCREW TERMINALS OR OPTIONAL CONNECTOR</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>0 TO 50V</td> <td>0 TO 300V</td> </tr> <tr> <td>0 TO 130V</td> <td>0 TO 500V</td> </tr> <tr> <td>0 TO 150V</td> <td>0 TO 600V</td> </tr> <tr> <td>0 TO 270V</td> <td></td> </tr> </table>	0 TO 50V	0 TO 300V	0 TO 130V	0 TO 500V	0 TO 150V	0 TO 600V	0 TO 270V	
0 TO 50V	0 TO 300V									
0 TO 130V	0 TO 500V									
0 TO 150V	0 TO 600V									
0 TO 270V										
	<p><b>SERIES S190</b> ▶ <a href="#">Data Sheet</a></p> <p>INDUSTRIAL GRADE; OUTPUT 0 TO 10VDC; ACCURACY 2%FS; RESPONSE 200m-SEC; POWERED BY INPUT; FREQUENCY 47-63Hz (400Hz AVAILABLE); TEMPERATURE 0° TO +60°C; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>0 TO 130V</td> <td>0 TO 300V</td> </tr> <tr> <td>0 TO 150V</td> <td>0 TO 600V</td> </tr> <tr> <td>0 TO 270V</td> <td></td> </tr> </table>	0 TO 130V	0 TO 300V	0 TO 150V	0 TO 600V	0 TO 270V			
0 TO 130V	0 TO 300V									
0 TO 150V	0 TO 600V									
0 TO 270V										
	<p><b>SERIES V</b> ▶ <a href="#">Data Sheet</a></p> <p>UTILITY GRADE; OUTPUT 0 TO 1mADC; ACCURACY 0.25%FS; RESPONSE 400m-SEC; POWERED BY INPUT; FREQUENCY 47-1000Hz; TEMPERATURE -20° TO +70°C; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>0 TO 150V</td> <td></td> </tr> <tr> <td>0 TO 300V</td> <td></td> </tr> <tr> <td>0 TO 500V</td> <td></td> </tr> </table>	0 TO 150V		0 TO 300V		0 TO 500V			
0 TO 150V										
0 TO 300V										
0 TO 500V										
	<p><b>SERIES VX</b> ▶ <a href="#">Data Sheet</a></p> <p>PROCESS CONTROL; OUTPUT 4 TO 20mADC; ACCURACY 0.5%FS; RESPONSE 400m-SEC; LOOP POWER +10 TO 32VDC; FREQUENCY 47-1000Hz; TEMPERATURE -20° TO +70°C; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>0 TO 150V</td> <td></td> </tr> <tr> <td>0 TO 300V</td> <td></td> </tr> <tr> <td>0 TO 500V</td> <td></td> </tr> </table>	0 TO 150V		0 TO 300V		0 TO 500V			
0 TO 150V										
0 TO 300V										
0 TO 500V										
	<p><b>SERIES 101M3</b> ▶ <a href="#">Data Sheet</a></p> <p>HIGH RESOLUTION; OUTPUT 0 TO 5VDC; ZERO SUPPRESSED INPUT RANGE; ACCURACY 0.5%FS; RESPONSE 1/2-CYCLE OF AC; POWERED BY INPUT; FREQUENCY 57-63Hz; TEMPERATURE -40° TO +70°C; METAL CASE; BARRIER SCREW TERMINALS</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>90 TO 150V</td> <td></td> </tr> </table>	90 TO 150V							
90 TO 150V										
	<p><b>SERIES 102M3</b> ▶ <a href="#">Data Sheet</a></p> <p>FAST RESPONSE; OUTPUT 0 TO 5VDC; POWERED BY INPUT; ACCURACY 0.5%FS; ZERO SUPPRESSED INPUT RANGE; RESPONSE 1-CYCLE OF AC; FREQUENCY 340-440Hz; TEMPERATURE -40° TO +70°C; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>90 TO 175V</td> <td></td> </tr> <tr> <td>105 TO 130V</td> <td></td> </tr> <tr> <td>175 TO 225V</td> <td></td> </tr> </table>	90 TO 175V		105 TO 130V		175 TO 225V			
90 TO 175V										
105 TO 130V										
175 TO 225V										
	<p><b>SERIES 105</b> ▶ <a href="#">Data Sheet</a></p> <p>ZERO SUPPRESSED INPUT RANGE; OUTPUT 0 TO 5VDC; ACCURACY 0.5%FS; RESPONSE 1-CYCLE OF AC; POWERED BY INPUT; FREQUENCY 57-63Hz; TEMPERATURE -40° TO +70°C; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC VOLTAGE RANGES</b></p> <table border="0"> <tr> <td>390 TO 490V</td> <td></td> </tr> <tr> <td>455 TO 505V</td> <td></td> </tr> <tr> <td>430 TO 530V</td> <td></td> </tr> </table>	390 TO 490V		455 TO 505V		430 TO 530V			
390 TO 490V										
455 TO 505V										
430 TO 530V										

DATA SHEETS AT  
[www.a-a-c.com](http://www.a-a-c.com)

### DC VOLTAGE TRANSDUCER & DETECTOR






PAGE  
11 OF 13

TWO MODELS IN ORDER OF VOLTAGE RANGE

	<p><b>SERIES S657</b> ▶ <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT GRADE; OUTPUT 4 TO 20MADC PROPORTIONAL TO (±) INPUT ABSOLUTE VALUE; ACCURACY 1%FS OVER TEMP; ISOLATION 5KV; RESPONSE 5M-SEC; POWER +22 TO +26VDC; TEMPERATURE -40° TO +85°C; PLASTIC CASE; CONNECTOR AND MATING CONNECTORS INCLUDED</p>	<p><b>DC VOLTAGE RANGES</b> 0 TO ±150V    0 TO ±750V 0 TO ±300V    0 TO ±1200V 0 TO ±500V    0 TO ±1500V 0 TO ±2000V</p>
	<p><b>SERIES S631</b> ▶ <a href="#">Data Sheet</a></p> <p>RAIL TRANSIT GRADE; OUTPUT SPST RELAY (10A CONTACTS); AUTOMATIC RESET @ +365VDC; ACCURACY 1%FS; RESPONSE 110m-SEC; POWER +25 TO +45VDC; TEMPERATURE -25° TO +75°C; PLASTIC CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>DC VOLTAGE RANGE</b> 0 TO +800V</p> <p>RELAY TRIPS @ +375VDC ±2VDC</p>

### AC POWER TRANSDUCERS

FIVE MODELS IN ORDER OF POWER RANGE



	<p><b>SERIES W&amp;Q</b> ▶ <a href="#">Data Sheet</a></p> <p>UTILITY GRADE; 1φ AND 3φ WATT &amp; VAR TRANSDUCERS; FREQUENCY 60HZ (50 &amp; 400HZ AVAILABLE); OUTPUT 0 TO ±1mADC (±5V &amp; ±10VDC AVAILABLE); ACCURACY 0.25%FS; RESPONSE 400m-SEC; POWERED BY INPUT; TEMPERATURE -20° TO +70°C</p>	<p><b>AC POWER RANGES</b> 0 TO 6.5AAC AND 85 TO 140VAC</p> <p>1φ (2-WIRE)    ACCEPTS BALANCED 3φ (3-WIRE)    OR UNRESTRICTED 3φ (4-WIRE)    LOADS &amp; VOLTAGE</p>												
	<p><b>SERIES S73</b> ▶ <a href="#">Data Sheet</a></p> <p>0-115VAC OR 0-230VAC; OUTPUT 0 TO +5VDC; ACCURACY 2%FS; RESPONSE 400m-SEC; POWER 120VAC; FREQUENCY 57-63HZ; TEMPERATURE 0° TO +50°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC POWER RANGES</b></p> <table border="0"> <tr> <td>0 TO 1KW</td> <td>0 TO 10KW</td> <td>0 TO 40KW</td> </tr> <tr> <td>0 TO 2KW</td> <td>0 TO 15KW</td> <td>0 TO 50KW</td> </tr> <tr> <td>0 TO 2.5KW</td> <td>0 TO 20KW</td> <td>0 TO 60KW</td> </tr> <tr> <td>0 TO 5KW</td> <td>0 TO 30KW</td> <td>0 TO 100KW</td> </tr> </table>	0 TO 1KW	0 TO 10KW	0 TO 40KW	0 TO 2KW	0 TO 15KW	0 TO 50KW	0 TO 2.5KW	0 TO 20KW	0 TO 60KW	0 TO 5KW	0 TO 30KW	0 TO 100KW
0 TO 1KW	0 TO 10KW	0 TO 40KW												
0 TO 2KW	0 TO 15KW	0 TO 50KW												
0 TO 2.5KW	0 TO 20KW	0 TO 60KW												
0 TO 5KW	0 TO 30KW	0 TO 100KW												
	<p><b>SERIES 415A</b> ▶ <a href="#">Data Sheet</a></p> <p>80-150VAC OR 160-230VAC; OUTPUT 0 TO +5VDC; ACCURACY 2%FS; RESPONSE 400m-SEC; POWERED BY INPUT; FREQUENCY 57-63HZ; TEMPERATURE 0° TO +50°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC POWER RANGES</b></p> <table border="0"> <tr> <td>0 TO 1KW</td> <td>0 TO 10KW</td> <td>0 TO 40KW</td> </tr> <tr> <td>0 TO 2KW</td> <td>0 TO 15KW</td> <td>0 TO 50KW</td> </tr> <tr> <td>0 TO 2.5KW</td> <td>0 TO 20KW</td> <td>0 TO 60KW</td> </tr> <tr> <td>0 TO 5KW</td> <td>0 TO 30KW</td> <td>0 TO 100KW</td> </tr> </table>	0 TO 1KW	0 TO 10KW	0 TO 40KW	0 TO 2KW	0 TO 15KW	0 TO 50KW	0 TO 2.5KW	0 TO 20KW	0 TO 60KW	0 TO 5KW	0 TO 30KW	0 TO 100KW
0 TO 1KW	0 TO 10KW	0 TO 40KW												
0 TO 2KW	0 TO 15KW	0 TO 50KW												
0 TO 2.5KW	0 TO 20KW	0 TO 60KW												
0 TO 5KW	0 TO 30KW	0 TO 100KW												
	<p><b>SERIES 416A</b> ▶ <a href="#">Data Sheet</a></p> <p>320-560VAC; OUTPUT 0 TO +5VDC; ACCURACY 2%FS; RESPONSE 400m-SEC; POWERED BY INPUT; FREQUENCY 57-63HZ; TEMPERATURE 0° TO +50°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC POWER RANGES</b></p> <table border="0"> <tr> <td>0 TO 4KW</td> <td>0 TO 40KW</td> <td>0 TO 100KW</td> </tr> <tr> <td>0 TO 10KW</td> <td>0 TO 50KW</td> <td>0 TO 200KW</td> </tr> <tr> <td>0 TO 20KW</td> <td>0 TO 80KW</td> <td></td> </tr> </table>	0 TO 4KW	0 TO 40KW	0 TO 100KW	0 TO 10KW	0 TO 50KW	0 TO 200KW	0 TO 20KW	0 TO 80KW				
0 TO 4KW	0 TO 40KW	0 TO 100KW												
0 TO 10KW	0 TO 50KW	0 TO 200KW												
0 TO 20KW	0 TO 80KW													
	<p><b>SERIES S217</b> ▶ <a href="#">Data Sheet</a></p> <p>160-300VAC &amp; 320-480VAC; OUTPUT 0 TO +5VDC; ACCURACY 2%FS; RESPONSE 400m-SEC; POWERED BY INPUT; FREQUENCY 57-63HZ; TEMPERATURE 0° TO +50°C; APERTURE 3/4 INCH DIA; METAL CASE; BARRIER SCREW TERMINATIONS</p>	<p><b>AC POWER RANGES</b></p> <table border="0"> <tr> <td>0 TO 2-4KW</td> <td>0 TO 20-40KW</td> </tr> <tr> <td>0 TO 5-10KW</td> <td>0 TO 25-50KW</td> </tr> <tr> <td>0 TO 10-20KW</td> <td>0 TO 40-80KW</td> </tr> </table>	0 TO 2-4KW	0 TO 20-40KW	0 TO 5-10KW	0 TO 25-50KW	0 TO 10-20KW	0 TO 40-80KW						
0 TO 2-4KW	0 TO 20-40KW													
0 TO 5-10KW	0 TO 25-50KW													
0 TO 10-20KW	0 TO 40-80KW													

DATA SHEETS AT  
[www.a-a-c.com](http://www.a-a-c.com)

### FREQUENCY TRANSDUCERS

TWO MODELS IN ORDER OF FREQUENCY RANGE

PAGE  
12 OF 13

	<p>SERIES <b>S350L</b></p> <p>► <a href="#">Data Sheet</a></p> <p>FLIGHT TEST; OUTPUT 0 TO 5VDC; LINEARITY 0.1%FS; INPUT VOLTAGES FROM 20MV TO 50V-RMS; RESPONSE =30/FREQUENCY; POWER +22 TO +30VDC; TEMPERATURE -48° TO +74°C; METAL CASE; CONNECTOR TERMINATIONS</p>	<p><b>FREQUENCY RANGES</b></p> <table border="0"> <tr> <td>100HZ</td> <td>1KHZ</td> <td>5KHZ</td> </tr> <tr> <td>200HZ</td> <td>2KHZ</td> <td>10KHZ</td> </tr> <tr> <td>300HZ</td> <td>3KHZ</td> <td>20KHZ</td> </tr> <tr> <td>500HZ</td> <td></td> <td></td> </tr> </table>	100HZ	1KHZ	5KHZ	200HZ	2KHZ	10KHZ	300HZ	3KHZ	20KHZ	500HZ		
100HZ	1KHZ	5KHZ												
200HZ	2KHZ	10KHZ												
300HZ	3KHZ	20KHZ												
500HZ														
	<p>SERIES <b>S343</b></p> <p>► <a href="#">Data Sheet</a></p> <p>MIL GRADE; OUTPUT 0 TO 5VDC; ACCURACY 1%FS; RESPONSE 250M-SEC; POWERED BY INPUT; TEMPERATURE -40° TO +70°C; RANGE &amp; ZERO ADJUSTMENTS; METAL CASE; CONNECTOR TERMINATIONS</p>	<p><b>FREQUENCY RANGES</b></p> <p>360 TO 440HZ @ 102-127VAC 360 TO 440HZ @ 200-250VAC AVAILABLE FIELD ADJUSTMENTS RANGE (±3%) &amp; ZERO (±3%)</p>												



Since 1965 we have continued to strive toward higher levels of product performance, quality and service. AAC provides AC & DC current, voltage, power and frequency transducers for: Industrial automation; laboratory; rail transit; land vehicles; shipboard; aircraft, missile and space flight applications. Products in this catalog represent only part of a broad line of measurement and control instrumentation. In addition, there are numerous and diverse variations available for unique applications.

New and innovative products are continually being developed to meet customer requirements. Product designs focus on the user's needs and our customers demand for competitive prices and quick delivery. This is the reason we offer a wide product selection from stock and continue to develop application specific modifications and custom products.

The fast delivery of cost effective products is due to:

- ① State of the art CAD engineering from circuit analysis with one day prototype pcb to mechanical design.
- ② Computerized inventory for quick access to parts and materials.
- ③ Up-to-date in house manufacturing including: coil winding, automated surface mount technology, encapsulation and more.
- ④ In house testing – EMI testing to DO-160, Mil-Std 981 and EN50155, random vibration, mechanical shock, thermal vacuum, high-energy pulse testing, high current and high voltage testing.

**5-YEAR WARRANTY:** AAC warrants all the products in this catalog to be free from defects in material and workmanship. The warranty applies to the product or parts thereof returned to AAC, with transportation charges prepaid, within five years of the original date of delivery to the original purchaser. Our obligation is limited to servicing, adjusting or replacing, at AAC option, any product or part thereof. Returns to the factory must be authorized in advance. For products sold to a manufacturer that uses it within an assembly made for resale, the remaining warranty is transferable, providing the

Quality, reliability and safety are designed in and carefully monitored throughout each process from order entry to shipment. Systems are based on IPC industry standard plus calibration and metrology traceable to NIST. Many of our products are UL, CSA and EU recognized and come with a FIVE YEAR WARRANTY. AAC is a woman owned small business certified to ISO 9001:2008 & AS9100:2004(B).

Maintaining a long cherished reputation for outstanding customer service is considered an important priority. Every attempt is made to satisfy any reasonable request. AAC computerized tracking schedule continuously monitors customer orders and provides immediate status upon request. An experienced staff stands ready to assist with product selections and to recommend alternative instrumentation solutions.

#### AAC

American Aerospace Controls, Inc.  
570 Smith Street, Farmingdale  
New York 11735-1115 USA

Telephone: (631) 694-5100  
Toll Free: (888) 873-8559  
Facsimile: (631) 694-6739  
(631) 845-0766

E-Mail: [aac@rcn.com](mailto:aac@rcn.com)